



CRC AIR SENSOR CLEAN

Ref. : 10210

1. GENERAL DESCRIPTION

CRC Air Sensor Clean improves and restores the performance and reliability of Mass Air Flow sensors as used on modern injection engines. It cleans quickly and effectively, both the thermistor and the hot wire or hot plate. CRC Air Sensor Clean is a high purity, effective precision cleaning solvent designed to meet today's environmental challenges. Based on fast drying naphthenic solvents without chlorinated, glycol or ether components.

2. FEATURES

- Ensures an optimal performance of the injection engine at cold and warm start.
- Allows the injection system to get the right information to adjust the fuel mix during high load conditions of the engine.
- For automatic gear boxes, the "shift-gear" information is given in an accurate way.
- For fast cleaning action and removal of all contaminants setting down on the sensor.
- No ozone-depleting action (ODP = 0,00).
- Periodic planned application (especially after exchanging the air filter) keeps up the performance and prolongs the life expectancy of the sensor.
- Non-conductive and non-corrosive.
- Evaporates completely, leaving no residue.
- Safe for all metal surfaces, most rubbers, most plastics and coatings. Test before use on sensitive plastics, adhesive-mounted or stressed parts.
- Convenient 360° (upside-down) spray valve for aerosols.
- High purity CO₂ propellant, giving an active product content of 97%.

3. APPLICATIONS

Specially designed for Mass Air Flow sensors:

- Hot Wire type sensors
- Hot Plate type sensors

When the air filter is exchanged, it is recommended to clean the Air Flow Sensor with the Air Sensor Clean before putting the engine in operation again.

4. DIRECTIONS

- Highly flammable formulation. Do not spray on energized electrical equipment or circuits, de-activate before product application and extinguish all flames, pilot lights and heaters.
- Test before use on sensitive plastics, adhesive-mounted or stressed parts.
- Locate the sensor: mostly mounted between the air inlet filter of the engine and the inlet manifold.
- Disconnect the sensor from the electrical circuit.
- Mark the position of the sensor and its housing. Depending on the type of sensor and/or the way the sensor is built in, either dismount the complete unit, or dismount and take out the sensor from the housing.



Manufactured by :
CRC Industries Europe BVBA
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com





CRC AIR SENSOR CLEAN

Ref. : 10210

- Use the extension tube and spray liberally on the hot wire/plate and the thermistor. Allow running off. Be careful not to touch the sensitive hot wire/plate nor the thermistor or its connections with the extension tube, the aerosol or your fingers.
- Allow solvents to evaporate completely before building in the sensor again. Beware to put the sensor, o-ring or other gasket, in the right position. A small drop of CRC 5-56 on the O-ring or gasket (do not contaminate the other parts of the sensor with oil !) might help for an easy assembly.
- Connect the sensor back to the electrical circuit.
- A safety data sheet (MSDS) according to EU directive 91/155/EEC and amendments is available for all CRC products.

5. TYPICAL PRODUCT DATA (without propellant)

Appearance	: clear liquid
Odor	: typical
Distillation range	: 75-85°C
Flash point (closed cup ASTM D 56)	: < 0°C
Non-volatile matter	: < 100 ppm
Specific gravity @ 20°C	: 0,78
Kauri-Butanol value	: 75
Surface tension @ 25°C	: 24 mN/m
Evaporation rate (vs. ether = 1)	: 2,3
Vapor density (vs. air = 1)	: 3

6. PACKAGING

Aerosol: 12 x 200 ml

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 10210 03 1004 01
Date : 21 december 2005



Manufactured by :
CRC Industries Europe BVBA
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com

