

TEROSON VR 200

June 2014

PRODUCT DESCRIPTION

TEROSON VR 200 provides the following characteristics:

Technology	Non combustible disinfectant
Base	Aqueous basis

Use biozides safety. Please read the labelling and product information before usage. TEROSON VR 200 is an aqueous solution containing additives for destruction of bacteria and fungus spore in the automobile air conditioning systems. TEROSON VR 200 has an excellent long time effect, i.e. the active substances destroy the bacteria and fungus and prevent their development for an extended time period. TEROSON VR 200 is delivered as can or as bottle for use with Terosept2 machine.

APPLICATION AREAS

TEROSON VR 200 is used as an disinfectant for bacteria and fungus in the automobile air conditioning system. TEROSON VR 200 eliminates the musty and fusty smell in the car interior caused by fungus attack. It is not allowed to use it as a normal room spray. Besides the effect of immediate cleaning TEROSON VR 200 ensures a long time effect disinfection.

TECHNICAL DATA

(Typical Test Results)

Colour	colourless, transparent
Odour	alcoholically
Consistency	liquid
Density	0.93 to 1.03 g/cm ³ at 20°C
pH	6.9 to 7.1

PRELIMINARY STATEMENT

Prior to application it is necessary to read the **Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed.

Application

For application of TEROSON VR 200 with Terosept2 machine, please follow operating instructions which are obtained with Terosept2 machine.

ATTENTION

During the complete cleaning procedure no persons / animals is allowed to be in the car.

Cleaning should be performed only in well ventilated areas.

As soon as cleaning process is completed, leave the car with opened side windows for sufficient ventilation of the interior.

STORAGE

Frost sensitive	yes
Recommended storage temperature	10 to 25 °C
Shelf life	24 months

Disclaimer

Note:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.



TEROSON VR 200

June 2014

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Henkel AG & Co. KGaA

D-40191 Düsseldorf, Germany
Phone: +49-211-797-0
www.henkel.com

Henkel Central Eastern Europe GmbH

A-1030 Wien, Austria
Phone: +43-1711-040
www.henkel.com

Henkel & Cie AG

CH-4133 Pratteln, Switzerland
Phone: +41-61-825-7000
www.henkel.com

