



- 16 ports 10/100/1000Mbps with 2 Port SFP and 2 Gigabit Uplink PoE switch
- Fully IEEE802.3af/at standard compliant.
- The Max. PoE output for each port is up to 30W
- Supports PoE power up to 250W for all PoE ports
- Safe and reliable power to most of PoE end devices

16 Port Gigabit PoE Switch with 2 Port SFP and 2 Port Gigabit Uplink Ports

Overview

CNet 16 ports 10/100/1000Mbps unmanaged PoE switch provides power and data from a single point, using Power over Ethernet (PoE) over a single Cat-5 cable or above. CGS-1622SP series can be used for any 10/100/1000Mbps link with Gigabit Uplink at your service. In addition, the PoE switch automatically determines PoE requirements, speed, and duplex. It is easy to operate and reliable and supports each port MAX 30W.

This PoE switch is ideal for powering PoE devices such as IP cameras, WLAN access points, IP phones, office access control systems, and other PD devices and offers a line of high quality products that provide a total solution for Ethernet application in different environments.

Specifications

Model	CGS-1622SP	
Ports Description	POE Port	Port 1-16: Gigabit Auto-Negotiation RJ45
	Uplink Port	GE1-GE2 : Gigabit Auto-Negotiation RJ45
		SFP1 - SFP2 : Gigabit SFP Ports
POE Power	MAX Poe Output	30W
	Total Power Consumption	250W
	Poe Port Priority	Support
LED Indicators	PWR、 PoE MAX、 PoE Indicator、 Link/Act	
Processing Types	Store And Forward	
Transmission Model	IEEE802.3X Full-Duplex And Backpressure Half-Duplex	
Performance	Backplane Bandwidth	40Gbps
	Packet Forwarding Rate	29,8Mpps
	MAC Address	8K
Network Standard	IEEE802.3i 10 BASE-T IEEE802.3u 100 BASE-TX IEEE802.3x Flow Control IEEE802.3af Power Over Ethernet IEEE802.3at Power Over Ethernet IEEE802.3az EEE	
Input Voltage	AC 100~240V 50/60Hz	
Dimension	440mm(L) * 285mm(W) *44mm(H)	
Cable Requirements	UTP Cat5 or Above	
Environment	<i>Operating Temperature : -10°C~45°C</i>	
	<i>Storage Temperature : -20°C~70°C</i>	
	<i>Operating Humidity : 10%~90%</i>	
	<i>Storage Humidity : 5%~95%</i>	